

# Document made available under the Patent Cooperation Treaty (PCT)

International application number: PCT/GB05/000620

International filing date: 18 February 2005 (18.02.2005)

Document type: Certified copy of priority document

Document details: Country/Office: GB  
Number: 0403724.8  
Filing date: 19 February 2004 (19.02.2004)

Date of receipt at the International Bureau: 26 May 2005 (26.05.2005)

Remark: Priority document submitted or transmitted to the International Bureau in compliance with Rule 17.1(a) or (b)



World Intellectual Property Organization (WIPO) - Geneva, Switzerland  
Organisation Mondiale de la Propriété Intellectuelle (OMPI) - Genève, Suisse

PCI/689005/800620.



INVESTOR IN PEOPLE

The Patent Office  
Concept House  
Cardiff Road  
Newport  
South Wales  
NP10 8QQ

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.


In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.

Signed

Dated 12 May 2005





Patents Form 1/77

Patents Act 1977  
(Rule 16)




20FEB04 EB74706-1 000001  
P01/7700 0.00-0403724.8 CHEQUE

**Request for grant of a patent**

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

The Patent Office

Cardiff Road  
Newport  
South Wales  
NP10 8QQ



1. Your reference GCL/10128 GB

19 FEB 2004

2. Patent application number  
(The Patent Office will fill this part in)

0403724.8

3. Full name, address and postcode of the or of each applicant (underline all surnames)

S.A.V. United Kingdom Limited, Scandia House,  
131 Armfield Close, West Molesey, Surrey KT8 2JR  
and

8158016001

Patents ADP number (if you know it)

George McHugh, c/o S.A.V. United Kingdom Limited,  
Scandia House, 131 Armfield Close, West Molesey,  
Surrey KT8 2JR

8812588002

If the applicant is a corporate body, give the country/state of its incorporation

United Kingdom (S.A.V. United Kingdom Limited)

4. Title of the invention A commissioning module including an airtight housing

5. Name of your agent (if you have one)

Abel & Imray

"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)

20 Red Lion Street  
London  
WC1R 4PQ  
United Kingdom

Patents ADP number (if you know it)

174001

6. Priority: Complete this section if you are declaring priority from one or more earlier patent applications, filed in the last 12 months.

Country

Priority application number  
(if you know it)

Date of filing  
(day / month / year)

7. Divisionals, etc: Complete this section only if this application is a divisional application or resulted from an entitlement dispute (see note f)

Number of earlier UK application

Date of filing  
(day / month / year)

8. Is a Patents Form 7/77 (Statement of inventorship and of right to grant of a patent) required in support of this request?

Yes

Answer YES if:

- a) any applicant named in part 3 is not an inventor, or
- b) there is an inventor who is not named as an applicant, or
- c) any named applicant is a corporate body.

Otherwise answer NO (See note d)

Patents Form 1/77

## Patents Form 1/77

9. Accompanying documents: A patent application must include a description of the invention. Not counting duplicates, please enter the number of pages of each item accompanying this form:

Continuation sheets of this form

Description 12 ✓

Claim(s) 3 ✓

Abstract nil

Drawing(s) 2 +2

*Am*

10. If you are also filing any of the following, state how many against each item.

Priority documents

Translations of priority documents

Statement of inventorship and right to grant of a patent (Patents Form 7/77)

Request for a preliminary examination and search (Patents Form 9/77) 1 ✓

Request for a substantive examination (Patents Form 10/77)

Any other documents (please specify)

11. I/We request the grant of a patent on the basis of this application.

Signature(s)

*Abel & Imray*

Abel & Imray

Date 19/02/04

12. Name, daytime telephone number and e-mail address, if any, of person to contact in the United Kingdom
- Mr G Leila 0207 242 9984

### Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

### Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 08459 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered YES in part 8, a Patents Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign and date it.
- Part 7 should only be completed when a divisional application is being made under section 15(4), or when an application is being made under section 8(3), 12(6) or 37(4) following an entitlement dispute. By completing part 7 you are requesting that this application takes the same filing date as an earlier UK application. If you want the new application to have the same priority date(s) as the earlier UK application, you should also complete part 6 with the priority details.

A commissioning module including an airtight housing

The invention relates to a commissioning module including an airtight housing, for preventing, or at least  
5 minimising, the formation of condensate from moisture in the air in the vicinity of the commissioning module.

The invention provides a commissioning module including:

an assembly of fluid control elements including a main  
10 fluid supply port, a main fluid return port, a first fluid distribution port and a second fluid distribution port, the assembly of fluid control elements being operable to pass supply fluid from the main fluid supply port to the first fluid distribution port and to pass return fluid entering  
15 the second fluid distribution port to the main fluid return port, at a rate that may be varied by at least one of the fluid control elements,

a plurality of lengths of conduit connected to the ports of the assembly of fluid control elements,

20 a housing enclosing the assembly of fluid control elements, the periphery of the housing including respective apertures through which pass the plurality of lengths of conduit, the housing being airtight except for the apertures in its periphery and

25 a plurality of sealing members providing airtight seals between the apertures in the periphery of the housing and the respective lengths of conduit passing through the apertures.

In one arrangement, the sealing members include  
30 grommets.

In another arrangement, the sealing members include grommet sleeves.

In an alternative arrangement, the sealing members include cable glands.

Cable glands are threaded tubular members which are slid over the conduit on opposite sides of the aperture  
5 through which the conduit passes, and are screwed together to form a seal between the conduit and the aperture.

Preferably, the housing includes a lid, sealing means being included for effecting an airtight seal between the lid and the remainder of the housing.

10 Preferably, the assembly of fluid control elements includes elements operable to effect the flushing through of the assembly.

A commissioning module including an airtight housing, in accordance with the invention, will now be described by  
15 way of example only with reference to the accompanying drawings, in which:

Fig. 1 represents a perspective view of the exterior of the airtight housing of a commissioning module and the associated exterior conduits connected to the commissioning  
20 module and

Fig. 2 is a diagrammatic representation of the components of a commissioning module enclosed within the airtight housing, including fluid distribution (flow and return) conduits connected to the commissioning module.

25 Referring to Fig. 1 of the accompanying drawings, there is shown an airtight rectangular housing 100 including a main body 100a and a lid 100b which covers the open lower part (as viewed) of the main body 100a. The lid 100b is attached to the main body 100a by means of hinges (not  
30 shown) and two catches 202 and 203 provide a means of securing the lid 100b releasably to the main body 100a. Sealing means (not shown) is included at the interface

between the lid 100b and the main body 100a of the housing 100 and provides an airtight seal between the lid 100b and the main body 100a of the housing 100 when the lid 100b is closed and secured by the catches 202 and 203. A length of chain 201 is connected between the lid 100b and the main body 100a of the housing 100 and serves as a safety device, when the lid 100b is allowed to swing downwards, following the release of the catches 202 and 203. A second length of chain corresponding to the length of chain 201 may be provided on the opposite side of the housing 100. Access to the interior of the housing 100 is achieved by releasing the catches 202 and 203 and allowing the lid 100b to swing downwards, as viewed in the drawing.

The housing 100 is made of galvanised steel and includes internal thermal insulation. Other materials, including non-metals, are suitable materials for the housing 100.

A length of flow conduit 1 is connected for the delivery of working fluid to the commissioning module within the airtight housing 100, passing through a first aperture in the rear bulkhead (as viewed) of the housing 100, a first sealing member 101 providing an airtight seal between the first aperture and the flow conduit 1. A length of return conduit 35 is connected for the removal of the working fluid from the commissioning module within the airtight housing 100, passing through a second aperture in the rear bulkhead of the housing 100, and a second sealing member 102 provides an airtight seal between the second aperture and the return conduit 35.

A length of first fluid distribution conduit 110 is connected for delivery of the working fluid from the commissioning module within the airtight housing 100 to a



first service, for example, a fan coil, and a length of second fluid distribution conduit 310 is connected for return of the working fluid from the service to the commissioning module within the airtight housing 100. The lengths of first and second distribution conduits 110 and 310 pass through respective apertures in the front bulkhead (as viewed) of the airtight housing 100 and respective third and fourth sealing members 103 and 106 provide airtight seals between the lengths of conduit 110 and 310. There are also sealing members 104 and 107 providing airtight seals between respective lengths of third and fourth fluid distribution conduits 120 and 320 and the apertures in the airtight housing 100 through which the lengths of third and fourth fluid distribution conduits 120 and 320 pass.

Further, there are sealing members 105 and 108 providing airtight seals between respective lengths of fifth and sixth fluid distribution conduits 130 and 330 and the apertures in the airtight housing 100 through which the lengths of fifth and sixth fluid distribution conduits 130 and 330 pass.

When a chilled fluid, usually water, is carried and regulated by the assembly of components included in the commissioning module, the temperature of the fluid encourages water vapour in the air in the vicinity of the commissioning module to condense on components of the commissioning module. When a commissioning module without an airtight housing is positioned in a roof or floor space of a building, the condensate is likely to spread from the commissioning module into the roof or floor space. The presence of condensate in the roof or floor space of a building encourages the growth of moulds and fungi in the roof or floor space, representing serious damage to the fabric of the building. Further, moisture accumulating in a

floor space is likely to find its way to the level immediately below the floor space into, for example, ceiling-mounted tiles and other fixtures at the level immediately below the floor space.

5       The airtight condition of the housing 100 serves to confine any condensate formed on the commissioning module to being that corresponding to the moisture in the air in the housing 100, thereby preventing or, at least, minimising the formation of condensate outside the housing 100, from the  
10   air outside the housing 100.

      A further consideration is that matter which finds the presence of condensate congenial to growth is, at least, confined to the housing 100. Such matter may include organisms that are undesirable in air ingested by humans,  
15   since the organisms may be harmful to humans ingesting them. The airtight condition of the housing 100 serves to restrict mixing of the air in the airtight housing 100 and air outside the airtight housing 100, thereby preventing, or at least minimising, the transfer of, possibly, undesirable  
20   organisms from within the airtight housing 100 to the air outside the housing 100.

      Although the rectangular housing 100 described is a convenient shape for the airtight housing for the commissioning module, it will be understood that the  
25   airtight housing may be of any one of a variety of available shapes and may, in fact, be tailored to fit into a specific available space. The housing 100 may be hung from a ceiling or placed below raised floor panels.

      The commissioning module enclosed within the airtight  
30   housing 100 serves the function of providing working fluid, usually water, received by way of the flow conduit 1 to the first, third and fifth fluid distribution conduits 103, 104

and 105 and returning exhaust fluid by way of the second, fourth and sixth fluid distribution conduits 106, 107 and 108 to the return conduit 35, at rates that may be varied by the commissioning module.

5       The commissioning module also serves the purpose of effecting the initial cleaning (by flushing) of the network to which it is connected, and itself, following its installation with the network and, subsequently, effecting the setting-up of the appropriate rates of flow in the fluid  
10 distribution conduits 103 to 108, which form part of the network.

For the performance of its functions, the commissioning module may include:

15       a plurality of fluid distribution valves so connected together as to provide a first through-port communicating with a second through-port by way of a fluid passage, the fluid distribution valves including respective fluid outlet ports communicating with the fluid passage through fluid flow-control means,

20       a first isolating valve including an inlet port and an outlet port, the outlet port being connected to the first through port of the plurality of fluid distribution valves and the inlet port providing a fluid supply port of the commissioning module,

25       further isolating valve means including an inlet port and an outlet port, the inlet port being connected to the second through-port of the plurality of fluid-distribution valves and the outlet port being connected to a combined fluid-exhaust port of the commissioning module,

30       a plurality of fluid flow-regulating valves, the same in number as there are fluid-distribution valves, including respective inlet and outlet ports, the outlet ports being

connected to the combined fluid-exhaust port of the  
commissioning module,

5 a further fluid flow-regulating valve connected between  
the combined fluid-exhaust port and a further fluid exhaust  
port of the commissioning module,

flow-rate measuring means connected between the further  
fluid flow-regulating valve and the combined fluid-exhaust  
port of the commissioning module and

10 at least one drain-off cock connected to permit the  
draining of fluid from the commissioning module.

Referring to Fig. 2 of the accompanying drawings, the  
commissioning module within the airtight housing 100  
includes a first isolating valve 2, a strainer 4, a first  
drain-off cock 6, first, second, third and fourth fluid-  
15 distribution valves 7, 8, 9, and 10, a second isolating  
valve 16, a second drain-off cock 17, a third isolating  
valve 18, an automatic air vent 19, first, second, third and  
fourth orifice plates 21, 22, 23 and 24, first, second,  
third and fourth double regulating valves 25, 26, 27 and 28,  
20 a fifth orifice plate 29 and a fifth double regulating valve  
30. The commissioning module further includes a first and  
second test points 3 and 5 between which lie the strainer 4,  
a third test point 15 which is adjacent to a port of the  
second isolating valve 16 and a fourth test point 20 which  
25 is adjacent to a port of the third isolating valve 18.

The first isolating valve 2 has a fluid-inlet and a  
fluid-outlet port, the fluid-inlet port of the first  
isolating valve 2 providing a fluid-supply port for the  
commissioning module and being, in use, connected to the  
30 length of fluid-supply (or flow) conduit 1. The strainer 4  
has a fluid-inlet port and a fluid-outlet port. The fluid-  
outlet port of the first isolating valve 2 is connected to

the fluid-inlet port of the strainer 4. The fluid-outlet port of the strainer 4 is connected to a fluid-inlet port of a drain off cock 6 and the fluid-outlet port of the strainer 4 is also connected to the first fluid-distribution valve 7.

5        The fluid-outlet port of the strainer 4 is connected to the first through-port of the first fluid-distribution valve 7. The second through-port of the first fluid-distribution valve 7 is connected to the first through-port of the second fluid-distribution valve 8, the second through-port of the  
10       second fluid-distribution valve 8 is connected to the first through-port of the third fluid-distribution valve 9 and the second through-port of the third fluid-distribution valve 9 is connected to the first through-port of the fourth fluid-distribution valve 10. The output ports of the first,  
15       second, third and fourth fluid-distribution valves 7, 8, 9 and 10 are shown connected to supply fluid or fluid flow lines 11, 12, 13 and 14, respectively, for connection to a fluid-distribution system or network which may include the commissioning module.

20       Comparing Figs. 1 and 2, the fluid distribution conduits 103 to 105 of Fig. 1 correspond to the supply fluid lines 11 to 13, say, of Fig. 2, the module shown in Fig. 2 being, in fact, suitable for supplying fluid to four services whereas the module shown in Fig. 1 supplies only  
25       three services.

Referring to Fig. 2, the second through-port of the fourth fluid-distribution valve 10 is connected to the inlet port of the second isolating valve 16. The outlet port of the second isolating valve 16 is connected to the inlet port  
30       of a third isolating valve 18 and to the second drain-off cock 17. The outlet port of the third isolating valve 18 is connected to an automatic air vent 19.

The second isolating valve 16, which is usually shut, serves to separate the fluid-supply or fluid-flow part of a fluid-distribution system, which includes the commissioning module, from the fluid-exhaust or fluid-return part of the fluid-distribution system. When the second isolating valve 16 is open it serves as a bypass route between the fluid-supply and fluid-exhaust parts of the system. Consequently, the second drain-off cock 17, the third isolating valve 18 and the automatic air vent serve as components of the fluid-exhaust part of the fluid-distribution system.

A fluid-exhaust line 31 of a fluid-distribution system which includes the commissioning module is connected to the inlet port of the first orifice plate 21 which has an inlet port and an outlet port. The outlet port of the orifice plate is connected to the inlet port of the first double regulating valve 25 and the outlet port of the double regulating valve 25 is connected to the outlet port of the second isolating valve 16.

Further fluid-exhaust lines 32, 33 and 34 of the fluid-distribution system are connected to the respective inlet ports of the second, third and fourth orifice plates 22, 23 and 24. The outlet ports of the orifice plates are connected to the inlet ports of the double regulating valves 26, 27 and 28, respectively, and the outlet ports of the double regulating valves 26, 27 and 28 are connected to the outlet port of the second isolating valve 16 by means of a length of conduit 36 serving as a combined fluid-exhaust port. The outlet ports of the double regulating valves 25, 26, 27 and 28 are connected also to the inlet port of the fifth orifice plate 29. The outlet port of the fifth orifice plate 29 is connected to the inlet port of the fifth double regulating

valve 30 and the outlet port of the fifth double regulating valve 30 is connected to the fluid return conduit 35.

Comparing Figs. 1 and 2, the fluid distribution conduits 106 to 108 of Fig. 1 correspond to the fluid exhaust lines 31 to 33, say, of Fig. 2, the module shown in Fig. 2 being, as is indicated above, suitable for supplying fluid to four services whereas the module shown in Fig. 1 supplies only three services.

Alternative arrangements include the positioning of the second drain-off cock 17, the third isolating valve 18 and the automatic air vent 19 adjacent to the fourth double regulating valve 28 rather than as shown in Fig. 2 where the second drain-off cock 17, the third isolating valve 18 and the automatic air vent 19 are positioned adjacent to the first double regulating valve 25.

As is shown in Fig. 2, the fluid-distribution valves 7, 8, 9 and 10 are so grouped together as to form a fluid supply-manifold, the first through-port of the first fluid distribution valve 7 and the second through-port of the fourth fluid-distribution valve 10 providing through-ports of the fluid supply-manifold, there being a through-passage between those through-ports of the manifold.

Also as shown in Fig. 2, the first, second, third and fourth orifice plates 21, 22, 23 and 24 with the first, second, third and fourth double regulating valves 25, 26, 27 and 28 are so grouped together with appropriate connection components, including the length of fluid conduit 36, as to form a fluid exhaust-manifold.

The commissioning module functions as follows:

The fluid-distribution valves 7, 8, 9 and 10 supply a working fluid to respective heat exchangers by way of fluid supply lines 11, 12, 13 and 14 and the working fluid returns

from the heat exchangers by way of fluid exhaust lines 31, 32, 33 and 34. The exhaust flow of the working fluid passes through the orifice plates 21, 22, 23 and 24 to the double regulating valves 25, 26, 27 and 28 to the fifth orifice  
5 plate 29 and to the fifth double regulating valve 30. The fifth orifice plate 25 is used to measure the overall flow rate for the commissioning module (the pressure drop across an orifice plate is an indication of flow rate) and the orifice plates 21, 22, 23 and 24 are selected to measure the  
10 flow rates for the respective fluid supply-exhaust lines 11-31, 12-32, 13-33 and 14-34. The fifth double regulating valve 30 effects adjustment of the overall flow rate and the double regulating valves 25, 26, 27 and 28 effect the adjustment of the individual flow rates for the respective  
15 fluid supply-exhaust lines 11-31, 12-32, 13-33 and 14-34. The automatic air vent 19 operates to vent air from the system when the third isolating valve 18 is open. The strainer 4 serves as a filter and removes particulate material from the working fluid. The test points 3 and 5  
20 permit the monitoring of the pressure drop across the strainer 4, a rise in the pressure drop indicating the need to remove and clean the strainer 4. Closure of the first isolating valve 2 effects the shut-off of supply fluid for removal of the strainer 4 or for any other reason requiring  
25 the shut-off of supply fluid. The first and second drain-off cocks 6 and 17 permit the system to be drained of fluid when the first isolating valve 2 is shut.

The commissioning module permits the filling and pressure testing of a fluid distribution system to which it  
30 belongs by use of the test point 15 for monitoring the fluid supply pressure and the test point 20 for monitoring the fluid exhaust pressure. The fluid flow rates throughout the



fluid distribution system are balanced in order to ensure that all parts of the system receive an adequate proportion of the total flow from the supply by the use of the double regulating valves 25, 26, 27 and 28. The commissioning  
5 module itself is flushed and cleaned by opening the second isolating valve 16, the strainer 4 effecting the removal of dirt, and the system as a whole is flushed and cleaned by closure of the second isolating valve 16.

Specific benefits attributed to the commissioning  
10 module include:

The provision of the single strainer 4, the single bypass valve 16 and drain-off cocks 6 and 17 capable of serving a fluid-distribution system including several heat exchangers.

15 The strainer 4 may be omitted and flow-rate measurement devices other than orifice plates may be used. Also, any form of fluid-regulating valve could be used rather than double regulating valves. Although referred to as an air vent, the vent 19 would, of course, vent any gas in the  
20 fluid-distribution system.

The provision of the air vent 19 at a position permitting the venting of several heat exchangers.

The access points are few in number and commissioning of the fluid-distribution system, being executed principally  
25 from the commissioning module, is effected with reduced need for access to other parts of the system and, consequently, reduced disturbance to adjacent structures.

The working fluid is most usually water which is heated for a heating system and cooled for a cooling system, the  
30 heat exchangers being selected as appropriate according to whether heating or cooling is required.

## CLAIMS

1. A commissioning module including:

an assembly of fluid control elements including a main  
5 fluid supply port, a main fluid return port, a first fluid  
distribution port and a second fluid distribution port, the  
assembly of fluid control elements being operable to pass  
supply fluid from the main fluid supply port to the first  
fluid distribution port and to pass return fluid entering  
10 the second fluid distribution port to the main fluid return  
port, at a rate that may be varied by at least one of the  
fluid control elements,

a plurality of lengths of conduit connected to the  
ports of the assembly of fluid control elements,

15 a housing enclosing the assembly of fluid control  
elements, the periphery of the housing including respective  
apertures through which pass the plurality of lengths of  
conduit, the housing being airtight except for the apertures  
in its periphery and

20 a plurality of sealing members providing airtight seals  
between the apertures in the periphery of the housing and  
the respective lengths of conduit passing through the  
apertures.

25 2. A module as claimed in claim 1, wherein the sealing  
members include grommets.

3. A module as claimed in claim 1, wherein the sealing  
members include grommet sleeves.

30 4. A module as claimed in claim 1, wherein the sealing  
members include cable glands.

5. A module as claimed in any one of claims 1 to 4,  
wherein the housing includes a lid, sealing means being  
included for effecting an airtight seal between the lid and  
5 the remainder of the housing, when the lid is fitted.

6. A module as claimed in any one of claims 1 to 5,  
wherein the assembly of fluid control elements includes  
elements operable to effect the flushing through of the  
10 assembly.

7. A module as claimed in any one of claims 1 to 6,  
wherein the assembly of fluid control elements includes:

a plurality of fluid distribution valves so connected  
15 together as to provide a first through-port communicating  
with a second through-port by way of a fluid passage, the  
fluid distribution valves including respective fluid outlet  
ports communicating with the fluid passage through fluid  
flow-control means,

20 a first isolating valve including an inlet port and an  
outlet port, the outlet port being connected to the first  
through port of the plurality of fluid distribution valves  
and the inlet port providing a fluid supply port of the  
commissioning module,

25 further isolating valve means including an inlet port  
and an outlet port, the inlet port being connected to the  
second through-port of the plurality of fluid-distribution  
valves and the outlet port being connected to a combined  
fluid-exhaust port of the commissioning module,

30 a plurality of fluid flow-regulating valves, the same  
in number as there are fluid-distribution valves, including  
respective inlet and outlet ports, the outlet ports being

connected to the combined fluid-exhaust port of the  
commissioning module,

5 a further fluid flow-regulating valve connected between  
the combined fluid-exhaust port and a further fluid exhaust  
port of the commissioning module,

flow-rate measuring means connected between the further  
fluid flow-regulating valve and the combined fluid-exhaust  
port of the commissioning module and

10 at least one drain-off cock connected to permit the  
draining of fluid from the commissioning module.

8. A module substantially as herein described with  
reference to and as shown in the accompanying drawings.



COMMISSIONING MODULE      PERSPECTIVE




Fig. 1






Fig 2







